




APPLICATION CHART



	DPG125	DCDA125	DCDW125	DCDS125	DCDV125	DCDF125	DCW60
Dry Use 	●	●	●	●	●	●	●
Wet Use 	●	●	●	●	●		●
Porcelain Tiles	●	●	●	●	●		●
Ceramic Tiles		●	●	●	●		●
Slate		●		●	●		
Marble			●				●
Granite						●	
Terracotta		●	●	●			
Concrete						●	
Glazed Clinker				●			
Hard Tile		●			●		
Slim Slab	●	●	●	●			
Big Slab	●	●	●	●			
Mosaic Tiles				●			
Glass Mosaic	●			●			
Stone						●	●
Hard Bricks						●	
Cutting	●	●	●	●	●	●	●
Grinding	●						
Bevelling	●						

SPECIFICATIONS

	DPG125	DCDA125	DCDW125	DCDS125	DCDV125	DCDF125	DCW60
Blade Diameter	125mm / 5"	125mm / 5"	125mm / 5"	125mm / 5"	125mm / 5"	125mm / 5"	60mm
Bore Size	22.23mm / 7/8"	22.23mm / 7/8"	22.23mm / 7/8"	22.23mm / 7/8"	22.23mm / 7/8"	22.23mm / 7/8"	M14 Thread
Segment Width	30mm	10mm	10mm	7mm	10mm	12mm	6mm
Maximum RPM	12250RPM	12250RPM	12250RPM	12250RPM	12250RPM	12250RPM	10200RPM

-  = Ideal material for cutting
-  = Suitable material for cutting
-  = NOT suitable for cutting